

Thermoflex Warm Edge Spacer is Thermoseal Group's own-manufactured foam spacer. It is made with a pre-desiccated Silicone rubber compounded in-house at Thermoseal Group and has a bespoke barrier tape to help reduce moisture penetration into the unit and reduce gas loss throughout the lifetime of the unit.



### Black Thermoflex

Flexible Spacer with unique gas barrier tape.  
(Standard Reels)

Black	Code	Reels Meterage	Reel length (Ft)
6mm (1/4")	BFL003	460	1509
8mm (5/16")	BFL006	335	1099
10mm	BFL008	305	1000
7/16" (11.1mm)	BFL009	273	895
12mm	BFL011	245	803
1/2" (12.7mm)	BFL012	243	797
14mm	BFL013	215	705
14.5mm	BFL014	215	705
16mm (5/8")	BFL016	205	672
18mm	BFL018	185	606
3/4" (19.1mm)	BFL019	175	574
20mm	BFL020	155	508



### Black Thermoflex

Flexible Spacer with unique gas barrier tape.  
(Small Reels)

Black	Code	Reels Meterage	Reel length (Ft)
6mm (1/4")	BFL3020	40	131
8mm (5/16")	BFL3050	40	131
10mm	BFL3070	40	131
7/16" (11.1mm)	BFL308	20	65.6
12mm	BFL310	20	65.6
1/2" (12.7mm)	BFL311	20	65.6
14mm	BFL312	20	65.6
16mm (5/8")	BFL315	20	65.6
18mm	BFL317	20	65.6
3/4" (19.1mm)	BFL318	20	65.6
20mm	BFL319	20	65.6

### Black Thermoflex

Flexible Spacer with unique gas barrier tape.  
(Auto Reels)



Black	Code	Reels Meterage	Reel length (Ft)
6mm (1/4")	BFL003AUTO	1380	4527
8mm (5/16")	BFL006AUTO	1005	3297
10mm	BFL008AUTO	915	3001
7/16" (11.1mm)	BFL009AUTO	819	2687
12mm	BFL011AUTO	735	2411
1/2" (12.7mm)	BFL012AUTO	729	2391
14mm	BFL013AUTO	645	2116
16mm (5/8")	BFL016AUTO	615	2017
18mm	BFL018AUTO	555	1820
3/4" (19.1mm)	BFL019AUTO	525	1722
20mm	BFL020AUTO	465	1525

### Grey Thermoflex

Flexible Spacer with unique gas barrier tape.  
(Standard Reels)



Grey	Code	Reels Meterage	Reel length (Ft)
6mm (1/4")	BFL003G	460	1509
8mm (5/16")	BFL006G	335	1099
10mm	BFL008G	305	1000
7/16" (11.1mm)	BFL009G	273	895
12mm	BFL011G	245	803
1/2" (12.7mm)	BFL012G	243	797
14mm	BFL013G	215	705
14.5mm	BFL014G	215	705
16mm (5/8")	BFL016G	205	672
18mm	BFL018G	185	606
3/4" (19.1mm)	BFL019G	175	574
20mm	BFL020G	155	508



**Grey Thermoflex**  
Flexible Spacer with unique gas barrier tape.  
(Auto Reels)

Grey	Code	Reels Meterage	Reel length (Ft)
6mm (1/4")	BFL003GAUTO	1380	4527
8mm (5/16")	BFL006GAUTO	1005	3297
10mm	BFL008GAUTO	915	3001
7/16" (11.1mm)	BFL009GAUTO	819	2687
12mm	BFL011GAUTO	735	2411
1/2" (12.7mm)	BFL012GAUTO	729	2391
14mm	BFL013GAUTO	645	2116
16mm (5/8")	BFL016GAUTO	615	2017
18mm	BFL018GAUTO	555	1820
3/4" (19.1mm)	BFL019GAUTO	525	1722
20mm	BFL020GAUTO	465	1525




**Grey Thermoflex**  
Flexible Spacer with unique gas barrier tape.  
(Small Reels)

Grey	Code	Reels Meterage	Reel length (Ft)
6mm (1/4")	BFL3020G	40	131.2
8mm (5/16")	BFL3050G	40	131.2
10mm	BFL3070G	40	131.2
7/16" (11.1mm)	BFL308G	20	65.6
12mm	BFL310G	20	65.6
1/2" (12.7mm)	BFL311G	20	65.6
14mm	BFL312G	20	65.6
16mm (5/8")	BFL315G	20	65.6
18mm	BFL317G	20	65.6
3/4" (19.1mm)	BFL318G	20	65.6
20mm	BFL319G	20	65.6

**Black Thermoflex Dual Seal Spacer**

Flexible Spacer with stepped profile for application of PIB.  
(Auto Reels - 6.3mm Profile Height)




Black	Code	Reels Meterage	Reel length (Ft)
8mm (5/16")	BFL400	884	2900
3/8" (9.5mm)	BFL406	TBC	TBC
10mm	BFL404	732	2401
7/16" (11.1mm)	BFL407	TBC	TBC
12mm	BFL408	610	2001
1/2" (12.7mm)	BFL410	549	1801
14mm	BFL412	526	1725
16mm (5/8")	BFL416	457	1500
18mm	BFL420	389	1276
3/4" (19.1mm)	BFL421	TBC	TBC
20mm	BFL424	366	1200

**Black Thermoflex Dual Seal Spacer**

Flexible Spacer with stepped profile for application of PIB.  
(Auto Reels - 7.3mm Profile Height)




Black	Code	Reels Meterage	Reel length (Ft)
8mm (5/16")	BFL460	672	2204
3/8" (9.5mm)	BFL462	TBC	TBC
10mm	BFL464	629	2063
7/16" (11.1mm)	BFL466	TBC	TBC
12mm	BFL468	525	1722
1/2" (12.7mm)	BFL470	549	1801
14mm	BFL472	465	1725
16mm (5/8")	BFL476	450	1476
18mm	BFL480	389	1276
3/4" (19.1mm)	BFL482	TBC	TBC
20mm	BFL484	314	1030



### Grey Thermoflex Dual Seal Spacer

Flexible Spacer with stepped profile for application of PIB. (Auto Reels - 6.3mm Profile Height)

Grey	Code	Reels Meterage	Reel length (Ft)
8mm (5/16")	BFL400G	884	2900
3/8" (9.5mm)	BFL406G	TBC	TBC
10mm	BFL404G	732	2401
7/16" (11.1mm)	BFL407G	TBC	TBC
12mm	BFL408G	610	2001
1/2" (12.7mm)	BFL410G	549	1801
14mm	BFL412G	526	1725
16mm (5/8")	BFL416G	457	1500
18mm	BFL420G	389	1276
3/4" (19.1mm)	BFL421G	TBC	TBC
20mm	BFL424G	366	1200



### Grey Thermoflex Dual Seal Spacer

Flexible Spacer with stepped profile for application of PIB. (Auto Reels - 7.3mm Profile Height)

Grey	Code	Reels Meterage	Reel length (Ft)
8mm (5/16")	BFL460G	672	2204
3/8" (9.5mm)	BFL462G	TBC	TBC
10mm	BFL464G	629	2063
7/16" (11.1mm)	BFL466G	TBC	TBC
12mm	BFL468G	525	1722
1/2" (12.7mm)	BFL470G	549	1801
14mm	BFL472G	465	1725
16mm (5/8")	BFL476G	450	1476
18mm	BFL480G	389	1276
3/4" (19.1mm)	BFL482G	TBC	TBC
20mm	BFL484G	314	1030

### Thermoflex Test Kit

Helps determine the activity of the desiccant in your Thermoflex spacer.

Includes: Approved Vials (x4); Approved Humidity Indicator Cards (x5); Desiccant Activity Test Log



Desiccant Activity Test	Code
Thermoflex Test Kit	A452
Thermoflex Test Kit Glass Vials x 1	A453
Humidity Indicator Card x 10	B2831

### Thermoflex Manual Application Equipment

#### Thermoflex Shuttle Applicator

Applicator (SHU001) for use in manual application of foam spacer in the production of IG units.



Code  
B281



#### Liner Remover

The liner remover (LS100) is used to efficiently remove the liner tape covering the side adhesive on spacer systems for manual application of Thermoflex.

Code  
B2817

#### Thermoflex Reel Stand

Allows air-tight storage of foam spacer for minimal desiccant moisture exposure.



Code  
ST REEL STAND 1



#### Thermoflex Double Reel Stand

Allows air-tight storage of two standard reels of foam spacer for minimal desiccant moisture exposure.

Code  
ST REEL STAND 2

#### Thermoflex Assembly Board

For use in assembly of IG units to align glass panels with adjustable end stop.



Code  
SW6060



### **Thermoflex Airfloat Table**

With foot switch to change from floatation to glass holding.

Code

ST SUPERAIR  
THERM

Please order using the product codes and descriptions. If ordering for the first time, please contact: [sales@thermosealgroup.com](mailto:sales@thermosealgroup.com) for details of your Area Sales Manager.

For further information on the Thermoflex range see: [www.thermoflexwarmedge.com](http://www.thermoflexwarmedge.com)

Access our Downloads here:

